



WIDE  
OPEN



PRO FINISH

# BRAVO 1<sup>®</sup> XS

The Mercury Racing Pro Finish Bravo 1<sup>®</sup> XS outboard propeller offers excellent time-to-plane performance, strong mid-range punch, and awesome top-end speed for bass, flats, cat flats, and performance center-console bay boats. The dual Mercury Performance Vent System<sup>®</sup> (PVS<sup>®</sup>) holes enable the operator to fine tune the amount of venting needed for quick planing. The stainless steel prop, designed for use on Mercury V6 OptiMax, OptiMax XS and OptiMax Pro XS outboards, features four robust blades and a tuned exhaust tube. The shortened exhaust tube provides greater top-end speed, while minimizing stern lift for improved boat handling and performance.

Half-inch pitch models enable operators to precision tune performance-oriented bass boats and center consoles for maximum power and efficiency. And, for some applications, the half-inch pitch will offer additional bow lift for enhanced top speed as well. The new half-inch pitch offerings benefit on-plane performance, mid-range fuel economy and top speed for single-engine four stroke applications. The action of the Mercury Performance Vent System<sup>®</sup> can easily be adjusted by simply adding PVS<sup>®</sup> fittings.

PITCH	RIGHT-HAND
22"	831910L60
22.5"	8M0111147
23"	831910L80
23.5"	8M0100104
24"	831912L60
24.5"	8M0111148
25"	831912L80
25.5"	8M0100105
26"	831914L60
26.5"	8M0111149
27"	831914L80
27.5"	8M0100106
28"	831916L60
28.5"	8M0111150
29"	831916L80
29.5"	8M0100107
30"	831918L60
30.5"	8M0111151
31"	831918L80
31.5"	8M0100109

ALL MODELS 15.25" IN DIAMETER

Published February 2024  
© 2024 MERCURY RACING. All Rights Reserved. Reproduction in whole or in part without permission is prohibited. All models and specifications are subject to change without notice or without incurring obligations to modify previously manufactured products. All trademarks belong to Brunswick Corporation.



[MERCURYRACING.COM/PROPELLERS](https://www.mercuryracing.com/propellers)

