PRO FINISH

BRAVO I® FS

Designed for outboard and sterndrive applications, the Mercury Racing Bravo I® FS propeller delivers unmatched time-to-plane performance, mid-range punch, mid-range cruise and top-end speeds for outboard bass, flats, cat flats, bay boats, offshore center consoles and sterndrive deck and vee bottoms under medium to heavy load. The patented Mercury® Performance Vent System® (PVS®) enables operators to dial in a propeller for peak planing performance. The PVS® system works in concert with robust blades that are hand blended and balanced by our propeller lab artisans.

The tuned exhaust tube minimizes stern lift for enhanced bow lift, handling and overall boat performance. Four-stroke outboard and sterndrive applications will use the Bravo I® FS with all four vent holes plugged with solid PVS® fittings. Larger, heavier multiple engine applications may benefit by taking one or two fittings out for improved planing. To maintain similar engine operating rpm in single engine applications, switching from a Tempest® Plus to the Bravo I® FS would require a 1-inch increase in pitch. A switch from the Fury® and Revolution 4® to the Bravo I® FS would require a 2-inch increase in pitch.

PITCH	LEFT-HAND	RIGHT-HAND
20″	8M0090453	8M0090451
20.5″		8M0118469
21″	8M0090457	8M0090455
21.5″		8M0118471
22″	8M0071088	8M0064450
22.5″		8M0128332
23″	8M0071089	8M0064468
23.5″		8M0152624
24″	8M0071090	8M0064469
24.5″		8M0128333
25″	8M0071091	8M0064470
25.5″		8M0129397
26″	8M0071092	8M0064471
26.5″		8M0128334
27″	8M0071093	8M0064472
28″	8M0071094	8M0064473
28.5″		8M0129335
29″	8M0071095	8M0064475
30″	8M0071096	8M0064476
31″	8M0071097	8M0064477
32″	8M0104418	8M0104417
33″	8M0104420	8M0104419

ALL MODELS 15.25″ IN DIAMETER

MERCURYRACING.COM/PROPELLERS

MERCURY RACING